

TECHNICAL DATA SHEET

B-TECH TOGGLE 2103

Lubricant for toggles and machine general lubrication

DESCRIPTION Compound of highly refined high viscosity lubricants and special polymer additives used for toggles and machine general lubrication.

TECHNICAL DETAILS	<i>Physical form:</i>	homog. liquid	<i>Viscosity (40°C):</i>	appr.320 cSt
	<i>Colour:</i>	yellow-brown	<i>Solubility:</i>	insoluble in
	<i>Odour:</i>	typical		water
	<i>Density (20°C):</i>	appr.0.90 g/ml	<i>Flammability:</i>	non flammable

SPECIFICATIONS


	TEST	METHOD	STANDARD LIMIT
	<i>Appearance</i>	Vis. (AO/1)	homogen. yellow-brown liq.
	<i>Viscosity (40°C)</i>	Cann. Fenske (VI/2)	300 - 400 cSt


CHARACTERISTICS B-TECH TOGGLE 2103 is used wherever a high adhesion degree of the lubricant to the substrate is requested:


- toggle lubrication in high pressure die casting machines;
- chain lubrication;
- lubrication of lathes and tracks in metalworking.

B-TECH TOGGLE 2103 ensures:

- high efficiency thanks to its very low dropping tendency;
- effective protection against corrosion.

STORAGE  Store between +5 and max +40 °C, in closed container.

 Shelf life: 24 months, in the original unopened containers.

PACKAGING  Pail: 20 Kg net weight Drum: 180 Kg net weight.
IBC: 850 Kg net weight

FURTHER INFORMATION For information regarding safety, transport and disposal, refer to the Safety Data Sheet of the product.

The data in this technical information sheet correspond to the properties of the product at the time of the sale and with regard to the specified application. It is on the responsibility of the user to make sure that the product is suitable for the use to which he intends to destine it.