

HYDRAULIC FG-F 32

Synthetic Hydraulic Oils

**DESCRIPTION**

HYDRAULIC FG-F 32 is a synthetic lubricant for the food-processing industry.

RECOMMENDED APPLICATIONS

HYDRAULIC FG-F 32 is especially adapted for the lubrication of:

- Plain bearings, bearings
- Conveyor chains
- Hydraulic circuits particularly at low temperatures
- Cold industries: Canning factories, slaughterhouses, etc.
- Equipment exposed in the mountains

ADVANTAGES

- Excellent oxidation and evaporation stability at high temperatures.
- Reinforced anti-wear and anti-corrosion performance.
- Low pour point.

SPECIFICATIONS / APPROVALS

HYDRAULIC FG-F 32 is the lubricant of choice in cold industries.

HYDRAULIC FG-F 32 is NSF H1 certified. Registration number 147869.

TECHNICAL INFORMATIONS

CHARACTERISTICS	STANDARDS	HYDRAULIC FG-F 32	UNIT
Viscosity at 40 °C	ISO 3104	32	cSt
Viscosity at 100 °C	ISO 3104	6	cSt
Viscosity index	ISO 2909	130	
Pour point	ISO 3016	-50	°C
Flash Point	ISO 2592	240	°C
Four ball test	ISO 20623	0.50	mm
Temperature range		-50 to + 160	°C

The specifications are given for information purposes only and may need to change.