

SAFCO SPRAY 21

Degreasing Agent

DESCRIPTION

SAFCO SPRAY 21 is an excellent degreasing solvent specifically developed for surface cleaning and preparation processes in the presence of considerable levels of pollution. It is also well-suited for the removal of ink, oil and grease.

SAFCO SPRAY 21 has a high purity index and is suitable for cleaning polluted electrical equipment. It has no effect on most high density plastics and elastomers.

SAFCO SPRAY 21 is an aerosol. For a 25L jerrycan or a 200L drum need, the SAFCO KLEEN 21 cleaner is available.

RECOMMENDED APPLICATIONS

SAFCO SPRAY 21 can be used in plastic injection, mechanical engineering, maintenance workshops, precision engineering, aeronautics, electrical and electronic equipment industrial areas for the following applications :

Degreasing of mechanical and plastic parts

Excellent solvent for oil, grease and temporary protective products. Compatible with most plastics and elastomers, as well as metals, including plating or precious metals.

Cleaning off excess glue or resin

Very good diluent for most organic substances. Good solvent for glues, UV adhesives, plastics and non-reticulated resins.

Surface preparation prior to bonding or painting

Can be used to clean parts made of metal, certain plastics, composites and elastomers. Can be used to remove organic or inorganic pollution prior to surface treatment.

Brake and clutch cleaner

Excellent solvent for brake fluids, sludge, encrusted duct and metallic residues. Evaporation rate adapted to allow the cleaning agent to penetrate the entire braking system and to completely dissolve dust and dirt. Leaves no residue.

Maintenance in food processing environments

Product complies to US FDA and CFR 21 regulations, and with NSF standards. Can be used in food processing industries to clean and degrease all packaging and handling equipment.

ADVANTAGES

- Compatible with most plastics and elastomers.
- Quick evaporation time.
- Cleans part from oil, grease, ink, glue, resins or plastics residues.

PACKAGING

650 mL Aerosol – pack of 6

TECHNICAL INFORMATIONS

| CHARACTERISTICS | METHOD | UNIT | SAFCO SPRAY 21 |
|--------------------------|-------------|------|----------------|
| Aspect | Visual | - | Clear |
| Density at 25°C | ISO 12 185 | - | 0.750 |
| Flash point (closed cup) | NF EN 22719 | °C | 23 |
| Self-ignition point | ASTM E 659 | °C | 250 |
| Freezing point | ISO 3016 | °C | < -30 |
| Copper stripe corrosion | NF M 07015 | - | 1a |
| KB index | ASTM D 1133 | - | 90 |
| Evaporation rate | NF T 30 301 | min | 10 |

The specifications are given for information purposes only and may need to change.

PRECAUTIONS FOR USE

Considering the wide range of substrates used in industries, we recommend that users conduct compatibility tests with sensitive materials to degrease.

These compatibilities often depend on operating procedures and therefore also on the contact time between **SAFCO SPRAY 21** and plastic materials.

Aerosol under pressure. Protect against sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn even after use.

Do not spray on a flame or incandescent material.

Keep out from children.

Keep away from flames and sources of ignition – Do not smoke.

Don't use in vapor phase

Avoid any projection on clothe

Do not discharge into drains after use. Use in a ventilated area.