

(PREVIOUSLY SUPRACUT EVO 200 SERIES)

**SUPRACUT EVO G**

Neat Cutting Oils

**DESCRIPTION**

**SUPRACUT EVO G** is a chlorine and sulphur-free range of neat cutting oils designed for standard machining operations on ferrous and non-ferrous metals.

**APPLICATIONS**

**SUPRACUT EVO G** is a range of neat cutting oils designed for all standard machining operations on ferrous and non-ferrous metals.

**SUPRACUT EVO G** is particularly suitable for machining operations on aluminium, brass, copper and all types of steels. Its use can be extended to some fine blanking operations as well as roller-burnishing.

**ADVANTAGES**

- Wide range of applications
- Chlorine and active sulphur free
- Good anti-wear properties
- High flash point
- High viscosity index

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHODS	EVO 15 G	EVO 30 G
Color	-	ASTM D 1500	0.5	0.5
Density at 20°C	-	ISO 12.185	0.839	0.849
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	14.5	30
Copper stripe corrosion	-	ASTM D 130	1b	1b
Flash point	°C	ASTM D 92	192	230

These characteristics are given only for information and can be updated over time.

**HEALTH & SAFETY**

- Free from organo-chlorinated additives and active sulphur
- Formulated with INRS ND 2356-227-12 recommendations
- Good dermatological behavior
- Storage in a frost-free and dry place

**SERVICES AND EQUIPMENT**

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and in-use monitoring of your lubricants.