

SUPRACUT INO XG

Neat Cutting Oils

DESCRIPTION

SUPRACUT INO XG is a premium chlorine and sulphur-free range of neat cutting oils designed for all hard machining on non-ferrous and ferrous metals.

APPLICATIONS

SUPRACUT INO XG is a range of neat cutting oils best suited for machining stainless steel, titanium, hard steels, nickel alloys and hard metals.

SUPRACUT INO XG is well adapted for use at high feed rates, under heavy duty and with high-pressure spray systems.

ADVANTAGES

- Consumption optimization
- Reinforced lubricating and cooling power
- Excellent extreme-pressure properties
- High flash point
- Low volatility

TECHNICAL INFORMATION

TYPICAL CHARACTERISTICS	UNITS	STANDARDS	SUPRACUT INO 20 XG
Colour	-	ASTM D 1500	1.0
Specific Gravity at 20°C	-	ISO 12.185	0.843
Viscosity at 40°C	mm ² /s	ASTM D 445	22
Copper strip corrosion	-	ASTM D 130	1a
Flash point	°C	ASTM D 92	202

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free from organo-chlorinated additives, zinc and heavy metals
- Formulated with INRS ND 2356-227-12 recommendations
- Good dermatological behavior
- Storage in a frost-free and dry place

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and in-use monitoring of your lubricants.