

IRIX EVO CSX 460-2 FG

Calcium sulfonate complex thickened lubricating grease based on pharmaceutical grade white oil.

CLASSIFICATION

ISO 12924: L-XB(F)DHB2
DIN 51502: KP2N-20

APPLICATION

Suitable for food industries where lubricants may have incidental contacts with food stuff. Recommended for heavy loaded applications with low to medium speed bearings, such as pellet presses and compactors used to process pet food and animal feed.



BASE OIL	BASE OIL VISCOSITY AT 40 °C (cSt)	THICKENER	NLGI GRADE	TEMPERATURE RANGE (°C)	DROP POINT (°C)	4-BALL WELD LOAD (kg)	COLOUR
White oil	460	Calcium Sulphonate Complex	2	-20 to 140 (peaks of 180 °C)	> 280	660	brown

Extreme Pressure



NSF H1



Heavy Loads



High Temperature



Water Resistant

**IRIX INO LX 460-2**

High performance grease based on synthetic base stocks.

CLASSIFICATION

ISO 12924: L-XD(F)DIB2
DIN 51502: KPHC2N-40

APPLICATION

Suitable for heavily loaded bearings in low to medium speed applications, applications at elevated temperatures, and wet and corrosive environments. The grease is perfectly adapted to carry high loads and to resist vibrations and shock loads.



BASE OIL	BASE OIL VISCOSITY AT 40 °C (cSt)	THICKENER	NLGI GRADE	TEMPERATURE RANGE (°C)	DROP POINT (°C)	4-BALL WELD LOAD (kg)	COLOUR
Synthetic	460	Lithium Complex	2	-40 to 150 (peaks of 220 °C)	> 260	> 380	beige

Corrosion Protection



Extreme Pressure



Heavy Loads



High Temperature

